

# UNIVERSITY OF ESWATINI FINAL EXAMINATION PAPER

PROGRAMME: BSC

AGRICULTURAL AND BIOSYSTEMS

**ENGINEERING (ABE) II** 

**COURSE CODE: ABE 207** 

TITLE OF PAPER: LAND SURVEYING

TIME ALLOWED: TWO (2) HOURS

INSTRUCTIONS: ANSWER QUESTION ONE AND ANY TWO OTHER QUESTIONS.

DO NOT OPEN THIS PAPER UNTIL PERMISSION HAS BEEN GRANTED BY THE CHIEF INVIGILATOR

### SECTION I: COMPULSARY

#### **QUESTION ONE**

A) A land surveying student went for Field Attachment as part of his training internship to get practical skills at a sugarcane company in the Lowveld of Swaziland. He was assigned to advise small scale farmers that were getting technical advice from the company about the importance of field measurement and its applications in agriculture. As part of the assignment, the student demonstrated the use of pacing, a linear measurement method that is always available, provided the pace factor is known. The demonstration meant he had to establish his pace factor with farmers, where a known distance of 20.0 m was measured and then paced (Table 1). Calculate the pace factor of the student.

(4 marks)

Table 1. Pace factor establishment.

Pacing runs (x)	Distance (Paces)			
1 .	34			
2	37			
3	39			
4	40			
5	43			
otal	193			

B) i. Calculate the dimensions in meters (m) and the area in hectares (ha) of the maize field which was measured as reflected in Table 2. (10 marks)

Table 2. Field measurement by pacing

Dimension	Length (Paces)			
AB	300			
BC	200			
CD	300			
DA	200			

ii. The dimensions of the maize field could have been measured accurately and faster with an electromagnetic distance measurement (EDM). The EDM utilizes equation 1 to determine the distance in question.

$$Speed = \frac{Distance}{Time}$$
 (1)

Given that the speed was 100 m/s and it took 9.5 seconds for the signal to be returned to the emitter, calculate the distance that was measured by the EDM.

(5 marks)

[40 marks]

- C) i. If the student in (A) had to use a bicycle wheel odometer, explain what he/she was supposed to do before using it. (2 marks)
  - ii. Discuss briefly how the bicycle wheel or fabricated odometer could be used for linear measurement in land surveying.(9 marks)
- D) Describe the land surveying process stating the three (3) stages involved. (10 marks)

# SECTION II: ANSWER ANY TWO QUESTIONS

## **QUESTION TWO**

- A) i. What are the two methods that are used for booking levelling data in land surveying? (2 marks)
  - ii. What are the four (4) surveyor's level cross hairs or stadia that are used in levelling? (4 marks)
  - iii. Which two of these stadia are used for distance measurement? (2 marks)

iv. A land surveyor measured the length of a dam spillway using a surveyor's level.
 Calculate the length of the dam spillway, if the telescope reading of the levelling staff was as reflected in Figure 1.




Figure 1. Surveyor's level telescopic reading of the levelling staff

B) Complete the booking of the levelling data shown in Table 3.

(10 marks)

C) i. What is the other method of height measurement other than the clinometer?

(2 marks)

- ii. A land surveyor with an eyesight height (h) of 1.7 m took position at a survey station site 50.0 m away from a tree, whose height he was measuring. He used a clinometer to measure the height of the tree, whose angle of elevation was 10°. Calculate the height of the tree. (4 marks)
- iii. Briefly describe how a clinometer could be used to measure the height of a known object.

  (4 marks)

[30 marks]

1st SEM.2018/2019

Examination N0.:

Table 3. Road section; Cardiff hall

and the Education Centre: rise and fall method

Name of Surveyor: Mr. Vusi Msimango

Name and Location of Site: Road section between Cardiff hall and the Education Centre. UNESWA, Luyengo Campus.

Instrument Type and No.: Dumpy Level, A405

Weather: Partly cloudy.

Date: August, 2007

Back Sight	Intermediate Sight	Fore Sight	Rise	Fall	Reduced Level	Distance (m)	Remarks
0.450					730.000	0	BM 730.00 m AOD
	1.720			1.270	728.730	20.000	Staff Station A
	1.850			0.130		40.000	Staff Station B
	1.980			0.130	728.470	60.000	Staff Station C
1.450		2.090		0.110	728.360	80.000	Change Point @ staff station I Road section – Cardiff Hall
	1.680			0.230		100.000	Staff station E - Road
	1.855					120,000	Staff station F - Road
	2.040			0.185		140.000	Staff station G - Road
0.965		1.555	0.485		728.255	160.000	Change point at staff station H
	1.205			0.240	728.015	180.000	Staff station I- Road
	1.495			0.290	727.725	200.000	Staff station J - Road
	1.775			0.280	727.445	220.000	Staff station K - Road
	2.030				727.190	240.000	Staff station L - Road
	2.150				727.070	260.000	Staff station M - Road
		2.050	0.100		727.170		Staff station N. End of levelling - Education Centre.
2.865		5.695	0.585	3.415	727.170		audition Contro.
5,695			3.415		730.000		
2.830			2.830		2.830		


### **QUESTION THREE**

- A) i. What are the other two (2) methods of contouring besides the grid method? (2 marks)
  - ii. Discuss in detail how a topographic survey of a selected agricultural land site could be conducted using the grid method. (10 marks)
- B) The following contour map of a section of Neverland, in Terrabethea was surveyed by Nosihle Kunene in September, 1953. She was in the process of drawing the contour plan or map when priorities changed and it was thus left incomplete. Complete the contour map, clearly reflecting the following:
  - i. Boarder line.
  - ii. Title box (complete with all the expected information).
  - iii. North. (9 marks)
- C) i. Define the term offset as used in chain surveying. (1 mark)
  - ii. What are the three (3) methods of offset identification, location and measurement that are used in chain surveying? (3 marks)
  - Which of these methods is used for both offset position identification and position location?

    (1 mark)
  - iv. In an effort to determine the accuracy of measurement a land surveyor measured an offset that was 30 m x 40 m. Calculate what the check length was supposed to be if the measurement was accurate.

    (4 marks)

[30 marks]



### **QUESTION FOUR**

- A) i. What are the three (3) methods of slope measurement? (3 marks)
  - ii. An arable small community vegetable crop development site was identified using a topographic map where it was found to lie between contour lines 44.400 m and 42.000 m. The horizontal distance between the contour lines in question was found to be 15 cm. Calculate the slope of the development site if its map was eventually drawn using a scale of 1: 1000. (5 marks)
  - iii. In your opinion, was the development site suitable for arable crop farming?

(2 marks)

- B) i. What are the three (3) methods of computing areas from maps other than the Simpson and Trapezoidal's rule? (3 marks)
  - ii. The following chain surveying data were recorded in the field when chaining and measuring off-sets of a proposed road or track from a nearby embankment (Table 3). Compute the area between the road and the embankment using the Trapezoidal's rule. (5 marks)

Table 3. Embankment chaining field data.

Station	A	В	С	D	E	F	G	Н	I	J
Chainage (m)	0	15	30	45	60	75	90	105	120	135
Offset (m)	6.3	4.2	3.8	2.1	8.2	9.3	6.7	4.6	3.2	1.2

- C) i. What are the two (2) methods of height measurement other than the clinometer? (2 marks)
  - ii. A land surveyor with an eyesight height (h) of 1.7 m took position at a survey site 50.0 m away from the tree, whose height he was measuring. He used a clinometer to measure the height of the tree, whose angle of elevation was 10°. Calculate the height of the tree. (4 marks)
  - ii. Discuss briefly how a clinometer could be used to measure the height of a known vertical object in land surveying. (6 marks)

[30 marks]